

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number  
WO 2004/113879 A1

(51) International Patent Classification<sup>7</sup>: G01N 19/02

(21) International Application Number:  
PCT/GB2004/002389

(22) International Filing Date: 7 June 2004 (07.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0313970.6 17 June 2003 (17.06.2003) GB

(71) Applicant (for all designated States except US): SLI-  
PALERT LLP (GB/GB); 3 Homefield Road, Radlett,  
Hertfordshire WD7 8PX (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BAILEY, Malcolm  
[GB/GB]; c/o SlipAlert LLP, 3 Homefield Road, Radlett,  
Hertfordshire WD7 8PX (GB).

(74) Agent: SAUNDERS & DOLLEYMORE; 9 Rick-  
mansworth Road, Watford, Hertfordshire WD18 0JU  
(GB).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report  
— with amended claims

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: SURFACE FRICTION TESTING APPARATUS



(57) Abstract: Surface testing friction apparatus comprises a trolley (1) and an inclined ramp (15). The trolley and ramp are arranged such that a slider (12) on the trolley comes into contact with the surface (22) during a test run over a surface. The friction coefficient of which is to be determined, the mass of the trolley (1) length (L) and a height (H) of the ramp (15) are selected such that for a slider of given properties, materials and dimensions the critical film thickness for a wet surface is approximately 2µm.

WO 2004/113879 A1